

TECHNICAL INFORMATION

Content: 100% Vinyl
 Width: 54"
 Weight: 28 oz./linear yard

Backing: 100% Brushed Polyester Knit
 Finish: Resilience^{SR}
 Cleanability: WS

Approx. Repeat: None
 Directional: No
 Railroaded: No

PERFORMANCE

Test Method	Results
Surface Abrasion: Heavy Duty A *	ASTM D-3597/4157 (Cotton Duck) Passes 651,000 Double Rubs
Breaking Strength: ☆*	CFFA-17/ASTM D-751 Exceeds Warp 79 lbs/Fill 56 lbs
Colorfastness to Light: ☆*	CFFA-2/ASTM G26 Method C 500 Hours

FLAMMABILITY **🔥***

California Technical Bulletin 117, Section E (Equivalent to BIFMA) Passes
 NFPA 260 (Equivalent to UFAC) Class 1 Passes
 FMVSS 302 Passes
 IMO A.652(16) 8.2 & 8.3 Passes
 May comply with California Technical Bulletin 133 when combined with appropriate components.

CARE AND CLEANING INFORMATION

WS: Water/Solvent Cleaner – Spot clean, with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding.

Prompt cleaning is always recommended. Recommended cleaning steps are listed by type of stain. For best results follow steps in order.

Recommended Care and Cleaning Steps

- Step 1: Mild soap and water, then rinse with fresh water and wipe dry with a clean cloth.
- Step 2: Wipe affected area with a soft cloth or soft bristle brush using a non-abrasive cleaner, i.e. Formula 409 or Fantastik. Rinse with fresh water and wipe dry.
- Step 3: 10% solution of household bleach and water. Rinse with fresh water and wipe dry.
- Step 4: 25% solution of alcohol and water. Rinse with fresh water and wipe dry.
- Step 5: 25% solution of lighter fluid or nail polish remover and water. Rinse with fresh water and wipe dry.

Regular cleaning and Maintenance: Step 1 (*Dirt, Dust, Grime*)

Oils: Steps 1 & 2 (*Organic & Petroleum based*)

Food: Steps 1 & 2 (*Ketchup, Chocolate, Coffee, Tea, Juice*)

Healthcare: Steps 1, 2 & 3 (*Blood, Urine, Betadine*)

Difficult Stains: Steps 1, 2, 3, 4 & 5 (*Eye shadow/Mascara, Lipstick, Crayon, Grease, Mustard, Ink/Permanent Marker, Paint*)

NOTE: The use of commercial vinyl conditioners and protectants is NOT RECOMMENDED.



Resilience^{SR} represents the latest technology in Faux Leather and Vinyl Protection, enhancing performance where it is needed the most.

Stain Resistance: With proper care, materials treated with Resilience^{SR} can be easily cleaned and will guard against stains maintaining the desired surface appearance for years to come.

Anti-Microbial & Anti-Bacterial Protection: Products treated with Resilience^{SR} are engineered to inhibit bacterial growth, as well as fungus, mold and mildew spores, resulting in a more hygienic environment.

Abrasion Resistance: Resilience^{SR} provides additional wear properties and surface durability to any Vinyl or Faux Leather, thereby increasing the life of the material. Resilience^{SR} is not visible, and does not affect the hand of the material. Resilience^{SR} is engineered to last, even after repeated cleaning and wear. Specify Resilience^{SR} for the most demanding healthcare and hospitality applications.

Resilience^{SR} complies with ASTM G-21/CFFA 120 and AATCC 147/CFFA 300 inhibiting the growth of the following organisms:
 Aspergillus Niger Penicillium Pinaphilum Chaetomium Globosum Trichoderma Virens Aureobasidium Pullulans Staphylococcus Aureus
 Klebsiella Pneumoniae Salmonella Choleraesuis Pseudomonas Aeruginosa

The information in this cleaning guide refers to performance of Resilience in tests conducted under laboratory conditions. This information does not imply a specific guarantee and does not relieve the user from the responsibility of the proper and safe use of the product and referenced cleaning agents.

ADDITIONAL INFORMATION

Custom Capabilities: All patterns can be custom colored. Minimum yardage applies.

Memo Samples: Please keep this card intact. Individual memo samples can be ordered on our web site or by contacting customer service.

Color Matching: Mayer Fabrics always attempts to ship a satisfactory commercial match. Because of industry standard dye lot variation, colors may not match exactly.

Specifications: Specifications are correct at the time of printing. Current specifications are available on our web site.

For information or assistance with products or services, call us at 800.428.4415 or refer to our web site, www.mayerfabrics.com.

ACT Registered Certification Marks



MAYERFABRICS

GSA Contract # GS-28F-0022P