

TECHNICAL INFORMATION

Content: 85% Vinyl face
15% Polyester backing

Weight: 32 oz./linear yard

Width: 54"

Finish: None

Approx. Repeat: None

Directional: No

Railroaded: No

PERFORMANCE

Surface Abrasion: Heavy Duty ASTM D 4157
(Wyzenbeek/Cotton Duck)

Results

Exceeds 30,000 Double Rubs

Colorfastness to Crocking AATCC-8

Dry: Class 4 min / Wet: Class 4 min

Colorfastness to Light AATCC 16

Class 5 at 1000 hours

FLAMMABILITY

California Technical Bulletin 117-2013

NFPA 260/UFAC Class 1

FMVSS 302

May comply with California Technical Bulletin 133 when combined with appropriate components.

REDUCED ENVIRONMENTAL IMPACT

This product is GREENGUARD Certified for low chemical and particle emissions to UL standard UL 2818 and may contribute to LEED certification. For complete information visit mayerfabrics.com and UL.com/gg.

CLEANING INFORMATION

BC: Bleach Cleanable – 1 part bleach, 9 parts water = 10% bleach, 90% water solution. Do not clean/disinfect fabric for longer than 10 minutes using the 10% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

Refer to Mayer Fabrics website for additional cleaning information.

ADDITIONAL INFORMATION

Custom Capabilities: All patterns can be custom colored. Minimum yardage applies.

Specifications: Specifications are correct at the time of printing. Current specifications are available on our website.



This fabric meets or exceeds these ACT performance guidelines.
Certification Marks owned by ACT



MAYERFABRICS

