

## TECHNICAL INFORMATION

Content: 100% Solution Dyed Olefin  
 Width: 54"  
 Weight: 18 oz./linear yd.

Backing: Latex  
 Finish: Stain Repellent  
 Cleaning Code: WS

Approx. Repeat: None  
 Directional: Yes  
 Railroaded: No

## PERFORMANCE

| Test Method                             | Results                                                                                             |
|-----------------------------------------|-----------------------------------------------------------------------------------------------------|
| Surface Abrasion: Heavy Duty <b>A</b> * | ASTM-D-4157 (Wire Screen)<br>10 Year Warranty - Exceeds ACT Requirements for Extreme Wear Condition |
| Breaking Strength: ★★                   | ASTM-D-5034<br>Warp 275 lbs/Fill 280 lbs                                                            |
| Seam Slippage: ★★                       | ASTM-D-4034<br>Warp 55 lbs/Fill 65 lbs                                                              |
| Pilling Resistance: ★★                  | ASTM-D-3511<br>Class 5                                                                              |
| Colorfastness to Crocking: ●*           | AATCC-105<br>Dry: Class 4 min/Wet: 4 min                                                            |
| Colorfastness to Light: ★*              | AATCC-16 / QUV ASTM-G-53<br>400 Hours - Class 5                                                     |

Class in the colorfastness requirements is based on a numerical scale of 5 for negligible or no color transfer to 1 for severe color changes or color transfer.

## FLAMMABILITY

California Technical Bulletin 117, Section E (Equivalent to BIFMA) Passes  
 NFPA 260 (Equivalent to UFAC) Class 1 Passes  
 ASTM E84 Class 1 or A Passes  
 May comply with California Technical Bulletin 133 when combined with appropriate components.

## CLEANING INFORMATION

WS: Water/Solvent Cleaner – Spot clean, with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding.

## TEN YEAR WARRANTY

Duraweave™10 is covered by a 10-year limited performance warranty from the date of installation, when used for seating applications. Duraweave™10 seating upholstery fabric is warranted against wear through (i.e. the complete deterioration of the fabric's structure in a particular area) and color loss (i.e. no worse than step 4 on the gray scale for color change) if properly installed and maintained. This warranty does not cover damage due to abuse, misuse, vandalism, inadequate padding or abrasion from other seating components or furniture, use of improper cleaning agents or methods and use subsequent to ownership by the original purchaser. Mayer Fabrics can provide a copy of the manufacturer's warranty.

If Duraweave™10 seating upholstery fabric fails to perform during the 10-year warranty period, the affected area of fabric will be repaired or replaced including labor and materials upon written request of the customer.

Except as expressly provided herein, Mayer Fabrics makes no representation or warranties, express or implied, including, without limitation, any warranty of merchantability or fitness of its products for any particular purpose, and hereby disclaim the same.

## ADDITIONAL INFORMATION

**Custom Capabilities:** All patterns can be custom colored. Minimum yardage applies.

**Memo Samples:** Please keep this card intact. Individual memo samples and additional colors can be ordered on our web site or by contacting customer service.

**Color Matching:** Mayer Fabrics always attempts to ship a satisfactory commercial match. Because of industry standard dye lot variation, colors may not match exactly.

**Specifications:** Specifications are correct at the time of printing. Current specifications are available on our website.

**For information or assistance with products or services, call us at 800.428.4415 or refer to our web site. [www.mayerfabrics.com](http://www.mayerfabrics.com).**

**DURAWEAVE™ is a registered trademark of Mayer-Paetz, Inc. 1999.**

\*ACT® Registered Certification Marks



Water and Stain Repellent Finish



**MAYERFABRICS**

GSA Contract #GS-28F-0022P

☎ 317.267.2626 or 800.428.4415 ☎ 317.267.2629 or 877.7SAMPLE [www.mayerfabrics.com](http://www.mayerfabrics.com)

©2001 Mayer-Paetz, Inc.

361CD  50210